



IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L8-830-0-D-DIM-UNV_.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] GEN FROM BALLABS TEST NO. 19927.0
[TESTLAB] BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC
[ISSUEDATE] 2023-07-14
[MANUFAC] WILLIAMS INDOOR
[OTHER] H.E. WILLIAMS, INC - CARTHAGE, MO 64836
[LUMINAIRE] CONTINUOUS COVE LUMINAIRE @ 0 DEGREE
[MORE] WITH FROSTED ACRYLIC LENS
[LUMCAT] CX-3-08-L8-830-0-D-DIM-UNV
[LAMPCAT] 22 INCH LED ARRAYS
[_SEARCH_SOURCETYPE] LED
[_SEARCH_APPLICATION] INDOOR, CLASSROOM, EDUCATIONAL, ATRIUM
[_SEARCH_MOUNTING] COVE

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	3032
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	123
Total Luminaire Watts	24.64
Ballast Factor	1.00
CIE Type	Indirect
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.22 ft
Luminous Width (90-270)	3.69 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	0	0	0
55	0	0	0
65	0	0	0
75	0	0	0
85	0	0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L8-830-0-D-DIM-UNV_.IES

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>	<u>112.5</u>	<u>135.0</u>	<u>157.5</u>	<u>180.0</u>
0	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
5	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
10	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
15	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
25	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
30	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
35	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
40	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
45	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
50	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
55	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
60	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
65	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
70	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
75	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
80	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
85	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
90	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
95	1.565	2.347	8.606	50.073	58.680	60.244	54.768	54.768	56.332
100	39.902	59.462	84.499	127.530	145.525	135.354	125.965	127.530	132.225
105	160.391	180.733	185.427	211.246	227.677	230.024	215.941	213.594	215.941
110	270.708	269.143	276.185	295.745	299.657	327.041	311.393	303.569	296.527
115	341.906	350.512	361.466	368.507	376.331	416.234	393.544	387.285	383.373
120	423.275	431.099	445.182	452.224	462.395	498.385	478.825	477.260	466.307
125	503.862	515.598	522.639	539.069	550.805	568.018	565.671	562.541	547.676
130	582.883	607.138	604.790	622.785	632.174	648.604	649.387	647.822	627.480
135	653.299	685.377	678.335	701.025	712.761	731.538	722.149	729.973	708.066
140	724.497	752.663	754.228	770.658	783.959	807.430	797.259	793.347	783.959
145	788.653	809.778	819.166	831.685	847.332	871.587	862.198	849.680	853.592
150	847.332	874.716	879.411	890.364	907.577	940.437	924.789	905.230	920.095
155	911.489	935.743	938.090	943.567	964.692	995.205	979.557	957.650	970.951
160	961.562	987.381	982.687	985.816	1008.506	1034.325	1021.806	996.770	1005.376
165	995.987	1029.630	1025.718	1021.806	1042.149	1063.273	1050.755	1025.718	1030.413
170	1018.677	1049.972	1049.972	1047.625	1066.403	1082.833	1070.315	1038.237	1042.149
175	1021.806	1060.144	1065.620	1064.056	1082.833	1096.134	1081.268	1039.801	1041.366
180	1062.491	1062.491	1062.491	1062.491	1062.491	1062.491	1062.491	1062.491	1062.491

IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L8-830-0-D-DIM-UNV_.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	0.00	N.A.	0.00
0-30	0.00	N.A.	0.00
0-40	0.00	N.A.	0.00
0-60	0.00	N.A.	0.00
0-80	0.00	N.A.	0.00
0-90	0.00	N.A.	0.00
10-90	0.00	N.A.	0.00
20-40	0.00	N.A.	0.00
20-50	0.00	N.A.	0.00
40-70	0.00	N.A.	0.00
60-80	0.00	N.A.	0.00
70-80	0.00	N.A.	0.00
80-90	0.00	N.A.	0.00
90-110	268.44	N.A.	8.90
90-120	642.61	N.A.	21.20
90-130	1129.54	N.A.	37.30
90-150	2198.96	N.A.	72.50
90-180	3032.11	N.A.	100.00
110-180	2763.67	N.A.	91.10
0-180	3032.11	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	0.00
10-20	0.00
20-30	0.00
30-40	0.00
40-50	0.00
50-60	0.00
60-70	0.00
70-80	0.00
80-90	0.00
90-100	52.01
100-110	216.43
110-120	374.17
120-130	486.92
130-140	543.64
140-150	525.79
150-160	440.36
160-170	291.53
170-180	101.26


IES INDOOR REPORT
PHOTOMETRIC FILENAME : CX-3-08-L8-830-0-D-DIM-UNV_.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	95	95	95	95	81	81	81	81	56	56	56	32	32	32	10	10	10	0
1	87	83	79	76	74	71	68	65	48	47	45	28	27	26	9	9	8	0
2	79	72	66	62	67	62	57	53	42	40	37	24	23	22	8	7	7	0
3	72	63	56	51	61	54	49	44	37	34	31	21	20	18	7	6	6	0
4	65	56	48	43	56	48	42	37	33	29	26	19	17	16	6	6	5	0
5	60	49	42	36	51	42	36	32	29	25	22	17	15	13	5	5	4	0
6	55	44	36	31	47	38	32	27	26	22	19	15	13	11	5	4	4	0
7	50	39	32	27	43	34	28	23	23	19	17	14	11	10	4	4	3	0
8	47	35	28	23	40	30	24	20	21	17	14	12	10	9	4	3	3	0
9	43	32	25	20	37	28	22	18	19	15	13	11	9	8	4	3	3	0
10	40	29	22	18	34	25	19	16	17	14	11	10	8	7	3	3	2	0

POLAR GRAPH



Maximum Candela = 1096.134 Located At Horizontal Angle = 112.5, Vertical Angle = 175
1 - Vertical Plane Through Horizontal Angles (112.5 - 292.5) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (175) (Through Max. Cd.)