


BALLABS CERTIFIED TEST REPORT NO.: 20374.0 DATE 04/30/18  
PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO  
DESCRIPTION: GEN7 V18 LED 6" TALL HEATSINK 6" SQ FORMED HOUSING DOWNLIGHT  
ACRYLIC MED TIR OPTIC & 6" CAST WHITE FLUSH SHALLOW TRIM  
w/SOLITE LENS ADVANCE # XI050C140V054DSM5 @ 1125mA  
CATALOG NBR: 6PS-L40/835-DIM-UNV-L-M-OF-WH  
LAMP TYPE : BXRE-35E4000

## CANDLEPOWER DISTRIBUTION

VERT ANG	0	22.5	45	67.5	90	ZONAL LUMENS
0	8786.	8786.	8786.	8786.	8786.	
5	8610.	8555.	8552.	8528.	8496.	815.9
10	7742.	7722.	7713.	7741.	7721.	
15	6039.	6053.	6091.	6105.	6127.	1724.3
20	3810.	3817.	3840.	3882.	3782.	
25	1971.	2024.	2066.	2067.	2061.	945.9
30	1032.	1027.	1057.	1088.	1132.	
35	589.	608.	621.	636.	623.	388.0
40	362.	370.	383.	392.	387.	
45	247.	253.	264.	265.	262.	200.7
50	180.	180.	194.	186.	180.	
55	125.	125.	139.	133.	125.	117.1
60	84.	86.	98.	92.	86.	
65	61.	61.	68.	63.	61.	62.5
70	39.	40.	44.	42.	41.	
75	25.	25.	26.	25.	25.	26.8
80	14.	14.	17.	14.	14.	
85	3.	3.	4.	1.	3.	3.1
90	0.	0.	0.	0.	0.	



*[Handwritten signature]*

**NVLAP<sup>®</sup>**  
TESTING

NVLAP LAB CODE 200921-0

## LUMEN SUMMARY

ZONE	LUMENS	%LAMP	%FIXT	ZONE	LUMENS	%LAMP	%FIXT
0- 30	3486.	NA.	81.4	90-120	0.	NA.	.0
0- 40	3874.	NA.	90.4	90-130	0.	NA.	.0
0- 60	4192.	NA.	97.8	90-150	0.	NA.	.0
0- 90	4284.	NA.	100.0	90-180	0.	NA.	.0
TOTAL LUMINAIRE = 0-180				4284.	NA.	100.0	

IES SPACING CRITERIA: END= .6 DIAGONAL = .6 CROSS= .6

THIS BALLABS REPORT WITH THE USE OF THE NVLAP LOGO SHALL NOT BE USED BY THIS CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NVLAP, NIST, OR ANY AGENCY OF THE FEDERAL GOVERNMENT.

BALLABS CERTIFIED TEST REPORT NO.: 20374.0 DATE 04/30/18  
 PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO  
 DESCRIPTION: GEN7 V18 LED 6" TALL HEATSINK 6" SQ FORMED HOUSING DOWNLIGHT  
 ACRYLIC MED TIR OPTIC & 6" CAST WHITE FLUSH SHALLOW TRIM  
 w/SOLITE LENS ADVANCE # XI050C140V054DSM5 @ 1125mA  
 CATALOG NBR: 6PS-L40/835-DIM-UNV-L-M-OF-WH  
 LAMP TYPE : BXRE-35E4000

\*\*\*\*\*

VERT ANGLE	LUMINANCES-CD/SQ-M HORIZONTAL ANGLE		
	0	45	90
45	14896.	5988.	5941.
55	9338.	3062.	2762.
65	6125.	1501.	1339.
75	4139.	597.	573.
85	1536.	102.	77.

\*\*MAXIMUM BRIGHTNESSES NOT MEASURED\*\*

\*\*\*\*\*

#### ZONAL CAVITY COEFFICIENTS OF UTILIZATION

EFFECTIVE FLOOR CAVITY REFLECTANCE=.20

CEILING	.80				.70				.50				.30				.10		.00
WALL	.70	.50	.30	.10	.70	.50	.30	.10	.50	.30	.10	.50	.30	.10	.50	.30	.10	.00	
RCR																			
0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00	
1	1.14	1.12	1.10	1.08	1.12	1.10	1.08	1.06	1.06	1.04	1.03	1.02	1.01	1.00	.99	.98	.97	.95	
2	1.09	1.05	1.01	.98	1.07	1.03	1.00	.97	1.00	.97	.95	.97	.95	.93	.94	.93	.91	.90	
3	1.05	.99	.95	.91	1.03	.98	.94	.91	.95	.92	.89	.93	.90	.88	.91	.88	.87	.85	
4	1.00	.94	.89	.85	.99	.93	.88	.85	.90	.87	.84	.89	.85	.83	.87	.84	.82	.80	
5	.96	.89	.83	.80	.94	.88	.83	.79	.86	.82	.79	.84	.81	.78	.83	.80	.77	.76	
6	.92	.85	.79	.76	.91	.84	.79	.75	.82	.78	.75	.81	.77	.74	.80	.76	.74	.73	
7	.89	.81	.75	.72	.87	.80	.75	.72	.79	.74	.71	.78	.74	.71	.77	.73	.70	.69	
8	.85	.77	.71	.68	.84	.76	.71	.68	.75	.71	.67	.74	.70	.67	.73	.70	.67	.66	
9	.81	.73	.68	.64	.80	.72	.67	.64	.71	.67	.64	.71	.66	.64	.70	.66	.63	.62	
10	.78	.69	.64	.61	.77	.69	.64	.60	.68	.63	.60	.67	.63	.60	.66	.63	.60	.59	

TESTED IN ACCORDANCE WITH CURRENT IES PROCEDURES

BALLABS CERTIFIED TEST REPORT NO.: 20374.0 DATE 04/30/18  
PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO  
DESCRIPTION: GEN7 V18 LED 6" TALL HEATSINK 6" SQ FORMED HOUSING DOWNLIGHT  
ACRYLIC MED TIR OPTIC & 6" CAST WHITE FLUSH SHALLOW TRIM  
w/SOLITE LENS ADVANCE # XI050C140V054DSM5 @ 1125mA  
CATALOG NBR: 6PS-L40/835-DIM-UNV-L-M-OF-WH  
LAMP TYPE : BXRE-35E4000

\*\*\*\*\*

ELECTRICAL CHARACTERISTICS 120.08V .3718A 44.4900W

LUMINOUS EFFICACY (LUMENS / WATTS) = 96.3

TESTED IN ACCORDANCE WITH CURRENT IES STANDARDS  
UTILIZING ABSOLUTE PHOTOMETRY PER LM-79-08

