BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC.

1618 HEADLAND DR.
FENTON, MO 63026
(636) 343-6006
(636) 343-6051 FAX

SIGNIFICANCE OF THE TEST IS LIMITED TO THE DEGREE THAT THE TESTED SAMPLE IS REPRESENTATIVE. OTHER FACTORS AFFECT FIELD PERFORMANCE.

BALLABS CERTIFIED TEST REPORT NO.: 20796.0 DATE 05/02/19
PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO
DESCRIPTION: 2-192 LED 22"ARRAYS EACH ON ALUM HEATSINK 24x14"HIGHBAY LUMINAIRE w/CLEAR ACRYLIC LENSES OVER LEDS & CENTER DRIVER HOUSING 2-ADVANCE #XI095C275V054BSF1 @ 1550mA
CATALOG NBR: GP2-L150/840-W-CL-DIM-UNV
LAMP TYPE : MADE #10560120

CANDLEPOWER DISTRIBUTION

VERT ANG	HORIZONTAL ANGLE 0	22.5	45	67.5	90	ZONAL LUMENS
0	5185.	5185.	5185.	5185.	5185.	
5	5161.	5147.	5188.	5178.	5200.	493.8
10	5089.	5154.	5247.	5227.	5237.	
15	4964.	5053.	5174.	5205.	5153.	1452.1
20	4803.	5007.	5036.	4972.	4948.	
25	4588.	4768.	4773.	4814.	4850.	2207.2
30	4347.	4592.	4557.	4621.	4618.	
35	4026.	4285.	4313.	4333.	4378.	2690.7
40	3673.	3836.	3989.	4101.	4066.	
45	3278.	3466.	3638.	3752.	3759.	2783.1
50	2893.	3101.	3180.	3375.	3370.	
55	2426.	2650.	2874.	2846.	2885.	2473.0
60	1888.	2158.	2374.	2380.	2427.	
65	1373.	1653.	1827.	1779.	1552.	1667.8
70	866.	1234.	1304.	1107.	1124.	
75	440.	701.	703.	638.	546.	670.3
80	153.	306.	293.	331.	333.	
85	23.	102.	99.	78.	77.	89.8
90	0.	78.	110.	120.	113.	
95	0.	25.	159.	215.	223.	139.1
100	0.	6.	46.	108.	124.	
105	0.	0.	6.	21.	40.	12.4
110	0.	0.	0.	8.	9.	
115	0.	0.	0.	0.	0.	.0
120	0.	0.	0.	0.	0.	
125	0.	0.	0.	0.	0.	.0
130	0.	0.	0.	0.	0.	
135	0.	0.	0.	0.	0.	.0
140	0.	0.	0.	0.	0.	
145	0.	0.	0.	0.	0.	.0
150	0.	0.	0.	0.	0.	
155	0.	0.	0.	0.	0.	.0
160	0.	0.	0.	0.	0.	
165	0.	0.	0.	0.	0.	.0
170	0.	0.	0.	0.	0.	
175	0.	0.	0.	0.	0.	.0
180	0.	0.	0.	0.	0.	



NVLAP® TESTING
NVLAP LAB CODE 200921-0

LUMEN SUMMARY

ZONE	LUMENS	%LAMP	%FIXT	ZONE	LUMENS	%LAMP	%FIXT
0- 30	4153.	NA.	28.3	90-120	152.	NA.	1.0
0- 40	6844.	NA.	46.6	90-130	152.	NA.	1.0
0- 60	12100.	NA.	82.4	90-150	152.	NA.	1.0
0- 90	14528.	NA.	99.0	90-180	152.	NA.	1.0
TOTAL LUMINAIRE =				0-180	14679.	NA.	100.0

IES SPACING CRITERIA: END= 1.2 DIAGONAL = 1.3 CROSS= 1.3

THIS BALLABS REPORT WITH THE USE OF THE NVLAP LOGO SHALL NOT BE USED BY THIS CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NVLAP, NIST, OR ANY AGENCY OF THE FEDERAL GOVERNMENT.

BALLABS CERTIFIED TEST REPORT NO.: 20796.0 DATE 05/02/19
PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO
DESCRIPTION: 2-192 LED 22"ARRAYS EACH ON ALUM HEATSINK 24x14"HIGHBAY LUMINAIRE w/CLEAR ACRYLIC LENSES OVER LEDS & CENTER DRIVER HOUSING 2-ADVANCE #XI095C275V054BSF1 @ 1550mA
CATALOG NBR: GP2-L150/840-W-CL-DIM-UNV
LAMP TYPE : MADE #10560120

****

LUMINANCES-CD/SQ-M
HORIZONTAL ANGLE

VERT ANGLE	0	45	90
45	22168.	23000.	23769.
55	20224.	21796.	21882.
65	15531.	17990.	15281.
75	8130.	10309.	8011.
85	1244.	3024.	2362.

MAXIMUM BRIGHTNESSES NOT MEASURED

****

ZONAL CAVITY COEFFICIENTS OF UTILIZATION

EFFECTIVE FLOOR CAVITY REFLECTANCE=.20

CEILING	.80				.70				.50			.30			.10			.00
WALL RCR	.70	.50	.30	.10	.70	.50	.30	.10	.50	.30	.10	.50	.30	.10	.50	.30	.10	.00
0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.01	1.01	1.01	.99
1	1.10	1.06	1.02	.99	1.07	1.04	1.00	.97	.99	.97	.94	.95	.93	.91	.92	.90	.88	.86
2	1.01	.94	.88	.83	.99	.92	.87	.82	.88	.84	.80	.85	.81	.78	.82	.79	.76	.74
3	.93	.84	.76	.70	.91	.82	.75	.70	.79	.73	.68	.76	.71	.67	.74	.69	.66	.64
4	.86	.74	.66	.60	.83	.73	.66	.60	.71	.64	.59	.68	.63	.58	.66	.61	.57	.55
5	.78	.66	.57	.51	.76	.65	.57	.51	.63	.56	.50	.60	.54	.49	.59	.53	.49	.47
6	.72	.59	.50	.44	.70	.58	.50	.44	.56	.49	.44	.54	.48	.43	.53	.47	.43	.41
7	.66	.53	.44	.38	.64	.52	.44	.38	.50	.43	.38	.49	.42	.38	.47	.42	.37	.35
8	.61	.47	.39	.33	.59	.47	.39	.33	.45	.38	.33	.44	.37	.32	.43	.37	.32	.30
9	.56	.42	.34	.29	.54	.42	.34	.29	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26
10	.52	.38	.31	.25	.50	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23

TESTED IN ACCORDANCE WITH CURRENT IES PROCEDURES

BALLABS CERTIFIED TEST REPORT NO.: 20796.0 DATE 05/02/19
PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO
DESCRIPTION: 2-192 LED 22"ARRAYS EACH ON ALUM HEATSINK 24x14"HIGHBAY LUMINAIRE w/CLEAR ACRYLIC LENSES OVER LEDS & CENTER DRIVER HOUSING 2-ADVANCE #XI095C275V054BSF1 @ 1550mA
CATALOG NBR: GP2-L150/840-W-CL-DIM-UNV
LAMP TYPE : MADE #10560120

****

ELECTRICAL CHARACTERISTICS 119.93V .9814A 116.9500W

LUMINOUS EFFICACY (LUMENS / WATTS) = 125.5

TESTED IN ACCORDANCE WITH CURRENT IES STANDARDS
UTILIZING ABSOLUTE PHOTOMETRY PER LM-79-08