BUILDING ACOUSTICS & LIGHTING LABORATORIES, INC.
1618 HEADLAND DR.
FENTON, MO 63026
(636) 343-6006
(636) 343-6051 FAX

SIGNIFICANCE OF THE TEST IS LIMITED TO THE DEGREE THAT THE TESTED SAMPLE IS REPRESENTATIVE. OTHER FACTORS AFFECT FIELD PERFORMANCE.

BALLABS REPORT NO. : 19477.0 E DATE: 09/06/16
PREPARED FOR: H.E. WILLIAMS, INC - CARTHAGE, MO
DESCRIPTION: 2-192 LED 22"ARRAYS EACH ON ALUM HEATSINK 24X18"HIGHBAY LUMINAIRE WITH NO DIFFUSER/OPEN BOTTOM & CENTER DRIVER HOUSING 2 ADVANCE #XI095C275V054DNF1 @ 2.45A EACH
CATALOG NO.: GP2-L230/850-6CPI/5-15P WHITE-PROTOTYPE-DRV-120
LED : D5638D192C2560A8N50JRB

ELECTRICAL MEASUREMENTS

ELECTRICAL CHARACTERISTICS - OUTPUT FROM DRIVER TO LED BOARD

VOLT	AMPS	WATTS	PF
35.216	2.4489	86.241	1.000

The fixture was mounted and energized within a 25 degree C environment. The electrical measurements were taken once the sample luminaire reached thermal equilibrium.