



The sample template above is not to scale and is not intended for actual use on-site. Scaled template will be shipped with every pole or anchor bolt order.

SERIES	POLE BASE O.D. (IN)	BOLT CIRCLE		ANCHOR BOLTS		CONDUIT OPENING (IN)	SQ. (IN)	BOLT SLOT SIZE (IN)
		MIN. DIA. (IN)	MAX. DIA. (IN)	PROJECTION (IN)	BOLT SIZE (IN)			
RSA	4	6.5	8.25	3.25	0.75 x 17	3.75	8.75	1 x 1.875
RSA	4.5	7	8.625	3.25	0.75 x 17	4.125	8.75	0.875 x 1.6875
RSA	5	7.5	9.5	3.25	0.75 x 17	4.5	9.25	1 x 2
RSA	6	8.75	10.25	3.5	0.75 x 17	5.5	10.25	1.125 x 1.875

RTA	4	6.5	8.25	3.25	0.75 x 17	3.75	8.75	1 x 1.875
RTA	5	7.5	9.5	3.25	0.75 x 17	4.5	9.25	1 x 2
RTA	6	8.75	10.25	3.5	0.75 x 17	5.5	10.25	1.125 x 1.875
RTA	7	10	11 ¹	4.125	1 x 36	6.5	11.1875	1.125 x 1.8125
RTA	8	11	12	4.125	1 x 36	7.5	12	1.125 x 1.6875
RTA	10 ²	14.5	14.5	4.75	1 x 36	9.5	13	1.125 x 1.875
RTA	10 ²	14.5	14.5	5.25	1.25 x 42	9.5	14	1.3125 x 1.8125

¹ Maximum bolt circle diameter changes to 11-1/4" for 30' to 50' poles.

² 0.250" wall or larger 10" base bolt circles have ± tolerances. Consult H.E. Williams, Inc. for actual range.