


Tandem In-Line Wiring



CONTINUOUS ROW FIXTURES

- Fully prewired for continuous row strips, industrials, suspended, and other Williams Fluorescent products.
- Polarized, quick-connect harnesses provide fast, error-proof wiring.
- Lamps down the row will be wired in tandem.

EXAMPLE **82 - 8 - 6 32 - C2BR - TW - EB4/2 - UNV**
 OPTIONS/
 ACCESSORIES

SINGLE FIXTURES

- Lamps wired/mounted in tandem.
- No harness required.

EXAMPLE **SDI3 - 8 - 4 32 - F - 128W - TW - EB2/2 - UNV**
 OPTIONS/
 ACCESSORIES

Master/Satellite System

ORDERING INFORMATION

1. Select the desired Williams recessed fixture.
2. Add the "MS_" option, as shown in the example below:
 - The example below accounts for one pair of fixtures.
 - Default wiring will be inboard/outboard where applicable.
 - When multiple ballasts are specified, standard wiring is inboard/outboard.

MASTER/SATELLITE ORDERING OPTIONS

Consult factory for other lengths and availability.

- MS9** Master/Satellite, 9' flex whip
- MS11** Master/Satellite, 11' flex whip

EXAMPLE **50 G - S 2 4 - 3 32 - S A12125 - MS9 - EB4/2 - UNV**
 OPTIONS/
 ACCESSORIES

