

# MEDIUM SHALLOW BACK TRAPEZOID

# WPTZ


**SUBMITTAL:**

**CFL**

**JOB:**

**TYPE:**

**VOLTAGE:**




**EXAMPLE:** **WPTZ - 2 42T - GX24q-4 - OPTIONS - UNV**

SERIES      # OF LAMPS      WATTAGE      LAMP BASE      OPTIONS/ACCESSORIES      VOLTAGE

## SERIES

### FEATURES

- ▶ Overall dimensions: 13-1/16" x 9-1/16" x 11-1/4".
- ▶ Dark bronze finish standard. Black or white finish available.
- ▶ Clear, heat and impact-resistant, tempered glass lens standard.
- ▶ Fully gasketed for wet locations.
- ▶ Provides full cutoff.
- ▶ Optional stainless steel wireguard, vandal shield, adjustable yoke mount and decorative lenses are available.
- ▶ 1/2" NPS threaded hub and plugged conduit entry points.



## WPTZ SERIES

**HOUSING** — Heavy-duty die-cast aluminum construction.

**REFLECTIVE SURFACES** — Two-piece hinged anodized aluminum reflector.

**LENS** — Heat and impact-resistant clear tempered glass standard. Etched glass or prismatic glass lenses also available.

## LAMP OPTIONS (Must specify)

### COMPACT FLUORESCENT

# LAMPS	WATTAGE	LAMP BASE
1, 2	26W	G24q-3
1, 2	32W	GX24q-3
1, 2	42W	GX24q-4



## ELECTRICAL

4-pin socket, electronic ballast standard. Prewired at factory for easy field installation. Rated 0°F minimum starting temperature.

## OPTIONS

<b>PC</b>	Factory-installed Photocell (120V, 208V and 277V only; must specify voltage)	<b>SF</b>	Single Fuse (120V or 277V only; must specify voltage)
<b>DF</b>	Double Fuse (208V or 240V only; must specify voltage)	<b>GMF</b>	HLR-GMF style slow blow fuse (Factory installed inside of unit. 120V & 277V only, must specify voltage)
<b>EG</b>	Etched Glass Lens	<b>PGL</b>	Prismatic Glass Lens
<b>WHT</b>	White Finish (RAL #9003)	<b>BLK</b>	Black Finish (RAL #9004)

## ACCESSORIES (Only one lens-mounted accessory per fixture)



## ACCESSORIES

Fixture is designed to accommodate only one lens-mounted accessory.

**PVS** Polycarbonate Vandal Shield  
**Y** Adjustable Yoke Mount

**WG** Stainless Steel Wireguard

## FINISH

Powder coated on heavy-duty die-cast housing. Dark bronze finish standard. Black or white finish available.

## VOLTAGE (Must specify)



<b>120</b>	120V	<b>208</b>	208V
<b>240</b>	240V	<b>277</b>	277V
<b>UNV</b>	120-277V		

## CFL

### MOUNTING

Wall mounts directly over a 4" maximum recessed outlet box.

### MOUNTING



BOLT CIRCLE PATTERN DETAIL

### LABELS

cCSAus Certified as luminaire suitable for wet location.

