

WALL LUMINAIRE

WL2


SUBMITTAL:

CFL

JOB:

TYPE:

VOLTAGE:



EXAMPLE: **WL2** - **2** **42T** - **GX24q-4** - **OPTIONS** - **UNV**

▼
▼
▼
▼
▼
▼

SERIES TOTAL LAMPS LAMP WATTAGE LAMP BASE OPTIONS/ACCESSORIES VOLTAGE


SERIES

This fixture does not comply with Buy American/ARRA and similar regulatory programs.



FEATURES

- ▶ Overall dimensions: 5-1/2" x 13" x 7-3/4".
- ▶ Heat and impact-resistant borosilicate glass lens for ultimate light distribution.
- ▶ Heavy-duty die-cast aluminum construction.
- ▶ 1/2" NPS threaded hub and plugged conduit entry points.
- ▶ Wet location listed.
- ▶ Dark bronze finish only.



WL2 SERIES

HOUSING — Die-cast aluminum with conduit access on bottom and back.

REFLECTIVE SURFACES — Aluminum reflector.

LENS — Molded prismatic borosilicate glass.

LAMP OPTIONS (Must specify)

COMPACT FLUORESCENT

# LAMPS	WATTAGE	LAMP BASE
1, 2	26Q	G24q-3
1, 2	32T	GX24q-3
1, 2	42T	GX24q-4

OPTIONS

GMF	HLR-GMF style slow blow fuse (Factory-installed inside of unit. 120V or 277V only; must specify voltage)	PC	Factory-installed photocell (120V, 208V, or 277V only; must specify voltage)
------------	--	-----------	--


ACCESSORIES

WG	Stainless steel wireguard
-----------	---------------------------


VOLTAGE (Must specify)

120	120V	208	208V
240	240V	277	277V
UNV	120-277V		

MOUNTING



BACK VIEW



BOLT CIRCLE PATTERN DETAIL

ELECTRICAL

Vertical lamp, 4-pin socket, electronic ballast standard. Prewired at factory for easy field installation. Rated 0°F minimum starting temperature. 4100K lamps are furnished, not installed.

FINISH

Powder coated finish on heavy-duty die-cast housing. Dark bronze finish only.

MOUNTING

Wall mounts directly over a 4" maximum recessed outlet box.

WL2

WALL LUMINAIRE

CFL

LABELS

cCSAus certified as
luminaire suitable
for wet locations.

