

DESIGNER WALL PACK – ROUND

WPRD


SUBMITTAL:

CFL

JOB:

TYPE:

VOLTAGE:



EXAMPLE:

WPRD - 1 42T - GX24q-4 - WD - OPTIONS - UNV

SERIES

OF WATTAGE LAMPS

LAMP BASE

DISTRIBUTION


OPTIONS

VOLTAGE

SERIES

FEATURES

- ▶ Overall dimensions: 18" x 9-3/16" x 9-1/16".
- ▶ Heat and impact-resistant tempered glass lens.
- ▶ Heavy-duty die-cast aluminum construction.
- ▶ Fully gasketed for wet locations.
- ▶ Provides full cutoff.
- ▶ Dark bronze finish only.



WPRD SERIES

HOUSING — Die-cast aluminum.

REFLECTIVE SURFACES — Aluminum reflector.

LENS — Tempered, flat, clear glass.

LAMP OPTIONS (Must specify)

COMPACT FLUORESCENT

# LAMPS	WATTAGE	LAMP BASE
1	26W	G24q-3
1	32W	GX24q-3
1	42W	GX24q-4

ELECTRICAL

4-pin socket, electronic ballast standard. Prewired at factory for easy field installation. Rated 0°F minimum starting temperature.

DISTRIBUTION (Must specify)

WD Wide Distribution

OPTIONS

SF Single Fuse (120V or 277V only; must specify voltage)

DF Double Fuse (208V or 240V only; must specify voltage)

GMF HLR-GMF Style Slow Blow Fuse (Factory installed inside of unit. 120V and 277V only; must specify voltage)


FINISH

Powder coated finish on heavy-duty die-cast housing. Dark bronze finish only.


VOLTAGE (Must specify)

120	120V	208	208V
240	240V	277	277V
UNV	120-277V		

MOUNTING



BACK VIEW



BOLT CIRCLE PATTERN DETAIL

MOUNTING

Wall mounts directly over a 4" maximum recessed outlet box.

LABELS

cCSAus certified as
luminaire suitable
for wet location.

