

4PR tunable WHITE


4.5" Shallow Plenum Downlight – Round

FIXTURE PERFORMANCE DATA

LED PACKAGE	DISTRIBUTION	DELIVERED LUMENS	WATTAGE	EFFICACY (lm/W)
L11	W	1025	14.6	70.4
	M	1193	14.6	82.0
	N	1184	14.6	81.4
L18	W	1664	24.0	69.3
	M	1936	24.0	80.7
	N	1922	24.0	80.1
L34	W	3097	46.7	66.3
	M	3504	46.7	75.0
	N	3482	46.7	74.5

MULTIPLIER TABLE


COLOR TEMPERATURE		
CCT	LUMENS	WATTS
2700K	0.83	1.03
3000K	1.00	1.00
3500K	0.99	0.99
4000K	1.00	1.00
5000K	0.98	1.03



- Photometrics tested in accordance with IESNA LM-79. Results shown are based on 25°C ambient temperature.
- Wattage shown is based on 120V input.
- Results based on 4000K, 80 CRI, actual lumens may vary +/-5%
- Use multiplier tables to calculate additional options.

PHOTOMETRY


4PR-TL-L18/8TW-DIM-UNV-LW-OF-WH Total Luminaire Output: 1664 lumens; 24.0 Watts | Efficacy: 69.3 lm/W | 80.0 CRI; 4051K CCT



CANDLEPOWER DISTRIBUTION	VERTICAL ANGLE	HORIZONTAL ANGLE	ZONAL LUMENS
		0°	
	0	1332	
	5	1241	113
	15	961	272
	25	842	384
	35	602	369
	45	276	221
	55	161	145
	65	94	94
	75	47	50
	85	12	14
	90	2	

LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 40	1138	68
	0 - 60	1505	90
	0 - 90	1664	100
	0-180	1664	100


4PR-TL-L18/8TW-DIM-UNV-LM-OF-WH Total Luminaire Output: 1936 lumens; 24.0 Watts | Efficacy: 80.7 lm/W | 80.0 CRI; 4051K CCT



CANDLEPOWER DISTRIBUTION	VERTICAL ANGLE	HORIZONTAL ANGLE	ZONAL LUMENS
		0°	
	0	4549	
	5	4319	392
	15	2698	732
	25	915	433
	35	274	179
	45	113	90
	55	59	53
	65	34	34
	75	17	19
	85	4	5
	90	1	

LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 40	1736	90
	0 - 60	1879	97
	0 - 90	1936	100
	0-180	1936	100

4PR-TL-L18/8TW-DIM-UNV-LN-OF-WH Total Luminaire Output: 1922 lumens; 24.0 Watts | Efficacy: 80.1 lm/W | 80.0 CRI; 4051K CCT



CANDLEPOWER DISTRIBUTION	VERTICAL ANGLE	HORIZONTAL ANGLE	ZONAL LUMENS
		0°	
	0	6450	
	5	5825	508
	15	2730	746
	25	729	351
	35	202	133
	45	95	75
	55	57	52
	65	34	34
	75	17	18
	85	4	5
	90	1	

LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 40	1738	90
	0 - 60	1864	97
	0 - 90	1922	100
	0-180	1922	100

TRIMLOCK DETAILS

TWIST



PULL




RELEASE




4PR tunable WHITE 4.5" Shallow Plenum Downlight – Round


TRIM TYPE DETAILS



FLANGE TYPE DETAILS




REFLECTOR FINISH DETAILS




MOUNTING TYPE DETAILS

NEW CONSTRUCTION




IC-RATED



LUMENS	LENGTH			
	A	B	C	D
L11	15-1/16"	16"	4-1/2"	12-1/8"
L18	15-1/16"	16"	6-3/8"	12-1/8"

REMODEL




4PR tunable WHITE


4.5" Shallow Plenum Downlight – Round

MOUNTING HARDWARE DETAILS


F1 2-Position fixed pan bracket, universal bar hanger included




BA1 Adjustable butterfly pan bracket, bar hanger not included




CA1 Adjustable caterpillar pan bracket, universal bar hanger included



F2 2-Position fixed pan bracket, t-bar bar hanger included



BA2 Adjustable butterfly pan bracket, heavy-duty universal bar hanger included



CA2 Adjustable caterpillar pan bracket, t-bar hanger included

