

CATALOG #: \_\_\_\_\_

TYPE: \_\_\_\_\_

PROJECT: \_\_\_\_\_

## FEATURES

- Ultra-bright, energy-efficient, long-life LEDs
- Fully automatic solid-state system on EM units recharges battery in 24 hours
- Compact, low-profile design
- Available as full-time AC powered unit or emergency unit with battery backup
- UV-stabilized ultra-clear acrylic edgelit panel provides consistent, uniform illumination
- Directional indicators can be installed on-site
- Charge rate/power on LED indicator and built-in test switch on emergency units
- 4.8V long-life, maintenance-free NiCd battery on EM units provides 90 minutes of emergency operation

## SPECIFICATIONS

- HOUSING** – Premium-grade extruded aluminum.
- ELECTRICAL** – Universal voltage, 120 or 277 VAC operation.
- MOUNTING** – Aluminum mounting canopy for ceiling, side, or wall mount installation.
- LISTINGS** –
  - UL 924 standard as an exit light suitable for dry or damp locations (0°C – 50°C).
  - Meets NFPA 101 Life Safety Code, NEC, OSHA, local and state codes.
  - Meets City of Chicago requirements.
- WARRANTY** – 5-year limited warranty, see [hew.com/warranty](http://hew.com/warranty).

## ORDERING EXAMPLE: EXIT/EL/CHICAGO - SF - WHT - AC - DA - D

### ORDERING INFO

SERIES	NUMBER OF FACES	HOUSING COLOR	POWER OPTIONS
EXIT/EL/CHICAGO	SF Single face DF Double face	WHT Industry-standard white BA Brushed aluminum	AC AC operation EM AC operation with emergency battery backup

### DIRECTIONAL ARROWS

EXIT SIGNAGE	
NA	No Arrows
DA	Double arrows
LA	Left arrows <sup>[1]</sup>
RA	Right arrows <sup>[2]</sup>
LARA	Left/Right arrow <sup>[3]</sup>

### VOLTAGE

D 120V or 277V

### STAIR SIGNAGE

SWNA	Stairs no arrow
SWDA	Stairs double arrows
SWRA	Stairs right arrow <sup>[4]</sup>
SWLA	Stairs left arrow <sup>[5]</sup>
SWLARA	Stairs left/right arrow <sup>[6]</sup>

## NOTES

- Single face only.
- Single face only.
- Double face only.

- Single face only.
- Single face only.
- Double face only.




# EXIT/EL/CHICAGO <sup>LED</sup> Chicago-Approved Edgelit

## ELECTRICAL INFORMATION


	INPUT WATTS (W)	INPUT AMPS (A)
120V	4.3	0.04
277V	4.7	0.02

## MOUNTING DETAILS

### CEILING MOUNT



### SIDE MOUNT



### WALL MOUNT

