

CATALOG #: \_\_\_\_\_

TYPE: \_\_\_\_\_

PROJECT: \_\_\_\_\_

**FEATURES**

- Tunable white from 3000K to 5000K CCT, minimum 80 CRI
- Low-profile depth for shallow plenum applications
- Diffuse lens provides smooth illumination for visual comfort
- Air return capability reduces number of unsightly ceiling vents for a cleaner appearance
- Surface mount kit preserves continuity
- Maximize energy savings with efficacies as high as 126 lm/W
- Made Right Here® in the USA

**SPECIFICATIONS**

- HOUSING/REFLECTOR – Precision die-formed 22-gauge C.R.S.
- SHIELDING – Frosted acrylic.
- FINISH – Highly reflective non-glare matte white polyester powder coat bonded to phosphate-free, multi-stage pretreated metal. All parts painted after fabrication to facilitate installation, increase efficiency, and inhibit corrosion.
- ELECTRICAL – High quality mid-power LED boards. L70 >50,000 hours per IES TM-21. Tunable White products use LEDs of multiple shade of white from single-CCT products at the same CCT. All CCTs are within 3 MacAdam ellipses.
- MOUNTING – NEMA Type “G”. Surface mount and drywall kit accessories available, ordered separately.
- LISTINGS –
  - cCSAus certified as luminaire suitable for dry or damp locations.
  - City of Chicago Environmental Air approved when specified with CP option.
- WARRANTY – 5-year limited warranty, see [hew.com/warranty](http://hew.com/warranty).

**ORDERING EXAMPLE: LT - 2 4 - L80/8TW - AF - OPTIONS - DALI - UNV**

**ORDERING INFO**

SERIES	WIDTH	LENGTH	LUMENS <sup>[1]</sup>	COLOR	SHIELDING
LT Static	1 1' <sup>[3]</sup>	2 2' <sup>[4]</sup>	1x4 L28 2,800lm L47 4,700lm L63 6,300lm	8TW Tunable white (80 CRI, 3000K-5000K)	AF Frosted acrylic
LT-AR Air Return <sup>[2]</sup>	2 2'	4 4'	2x2 L27 2,700lm L39 3,900lm L49 4,900lm		
			2x4 L50 5,000lm L64 6,400lm L80 8,000lm		

OPTIONS <sup>[5]</sup>	CONTROL <sup>[6]</sup>	VOLTAGE
EM/7WRM Remote mount 7-watt emergency battery <sup>[7]</sup>	DALI Driver prewired for DALI applications	120 120V 277 277V
EM/10W 10-watt emergency battery <sup>[8]</sup>	DIM Dimming driver with (1) 0-10V signal to control dimming and (1) 0-10V signal to control CCT	UNV 120-277V
EM/12W 12-watt emergency battery <sup>[9]</sup>	DMX Driver prewired for DMX applications	
EQCLIPS (L_) Earthquake clips <sup>[10]</sup>		
(L_) Additional lower lumen packages available. <sup>[11]</sup> Example: 5,800 lumens = LT-24-L64/8TW-(L58)		
CP Chicago Plenum (CCEA)		
LT-14-SMK-W Surface mount kit, 1'x4', white		
LT-22-SMK-W Surface mount kit, 2'x2', white		
LT-24-SMK-W Surface mount kit, 2'x4', white		
DFK-1248W Drywall kit, 12" x 48", white		
DFK-2424W Drywall kit, 24" x 24", white		
DFK-2448W Drywall kit, 24" x 48", white		

**NOTES**

- <sup>1</sup> Lumens based on 4000 CCT. Actual lumens may vary +/-5%, see page 2 for FIXTURE PERFORMANCE DATA. Additional lumen packages available, see options
- <sup>2</sup> Air return through side slots. Not available with surface mount or CP option.
- <sup>3</sup> 4' length only
- <sup>4</sup> 2' width only
- <sup>5</sup> See page 3 for SURFACE MOUNT KIT DETAILS. See Technical Info for Drywall Kit and Power Entry details.
- <sup>6</sup> See page 3 for CONTROL DETAILS.
- <sup>7</sup> 120-277V only
- <sup>8</sup> 120-277V only
- <sup>9</sup> 120-277V only
- <sup>10</sup> 4 per fixture; LT is compatible with Williams earthquake clips only.
- <sup>11</sup> Specify in increments of 100 nominal lumens. Option must be specified with next higher lumen package.




**FIXTURE PERFORMANCE DATA**

	LED PACKAGE	DELIVERED LUMENS	WATTAGE	EFFICACY (lm/W)
1x4	L28	2855	22.6	126.3
	L47	4721	39.6	119.3
	L63	6308	54.8	115.3
2x2	L27	2797	24.6	113.7
	L39	3901	32.5	120.1
	L49	4969	42.7	116.5
2x4	L50	5082	42.0	120.9
	L64	6443	54.7	117.7
	L80	8003	63.7	125.6

**MULTIPLIER TABLE**


CCT	CONVERSION FACTOR	
	LUMENS	WATTAGE
3000K	0.95	1.04
3500K	0.98	1.02
4000K	1.00	1.00
5000K	0.96	1.04



- Photometrics tested in accordance with IESNA LM-79. Results shown are based on 25°C ambient temperature.
- Wattage shown is average for 120V through 277V input.
- Results based on 4000K, 80 CRI, actual lumens may vary +/-5%
- Use multiplier table to calculate additional options.

**PHOTOMETRY**


**LT-14-L63/8TW-AF-DALI** Total Luminaire Output: 6308 lumens; 55 Watts | Efficacy: 115 lm/W | 82.7 CRI; 3494K CCT



VERTICAL ANGLE	HORIZONTAL ANGLE			ZONAL LUMENS
	0°	45°	90°	
0	2397	2397	2397	
5	2408	2404	2404	228
15	2266	2284	2305	645
25	2012	2064	2114	943
35	1658	1754	1850	1088
45	1318	1472	1606	1121
55	939	1110	1259	989
65	610	793	882	755
75	316	433	401	425
85	84	98	74	114
90	0	0	0	

LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 30	1815	29
	0 - 40	2903	46
	0 - 60	5013	80
	0 - 90	6308	100
	0 - 180	6308	100


**LT-22-L49/8TW-AF-DALI** Total Luminaire Output: 4969 lumens; 43 Watts | Efficacy: 116 lm/W | 84.9 CRI; 3544K CCT



VERTICAL ANGLE	HORIZONTAL ANGLE			ZONAL LUMENS
	0°	45°	90°	
0	1716	1716	1716	
5	1716	1704	1705	162
15	1637	1641	1656	464
25	1494	1517	1552	701
35	1268	1337	1407	836
45	991	1119	1222	859
55	710	872	1005	779
65	459	638	791	626
75	234	413	546	417
85	53	116	113	125
90	0	0	0	

LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 30	1328	27
	0 - 40	2163	44
	0 - 60	3802	77
	0 - 90	4969	100
	0 - 180	4969	100


**LT-24-L80/8TW-AF-DALI** Total Luminaire Output: 8003 lumens; 64 Watts | Efficacy: 126 lm/W | 84.9 CRI; 3544K CCT



VERTICAL ANGLE	HORIZONTAL ANGLE			ZONAL LUMENS
	0°	45°	90°	
0	2840	2840	2840	
5	2821	2823	2824	268
15	2661	2686	2712	763
25	2357	2430	2499	1125
35	1991	2121	2245	1326
45	1625	1834	2022	1390
55	1140	1386	1602	1230
65	735	1019	1251	990
75	367	652	826	668
85	107	260	249	244
90	0	0	0	


LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 30	2156	27
	0 - 40	3482	44
	0 - 60	6102	76
	0 - 90	8003	100
	0 - 180	8003	100

**CROSS SECTIONS**




**FIXTURE DETAILS**


**BACK VIEW**



**SIDE VIEW**



**AIR RETURN**



Total Air Return Space: 12-1/2" sq. (2x2) and 25-1/2" sq. (1x4 and 2x4)

**CONTROL DETAILS**

**DIM**



**DALI**




**DMX**



**SURFACE MOUNT KIT DETAILS**




**CROSS SECTIONS**




**BACK VIEWS**

**1x4**



**2x2**



**2x4**

