

2x2 | 2x4
Shown with RA lens

CATALOG #: _____

TYPE: _____

PROJECT: _____

FEATURES

- Easily change the color temperature on-site with fieldselecCCT[®] technology
- Three switchable CCT settings provide ultimate flexibility – 3000K, 3500K and 4000K
- Room-side access
- Ultra slim 2-3/8" for minimal plenum space
- Uniform ambient illumination
- Companion surface and retrofit kit preserve continuity, see hew.com
- Maximize energy savings with efficacies up to 123 lm/W
- Rated for direct contact with insulation
- Heavy duty C.R.S. construction
- Made Right Here™ in the USA

SPECIFICATIONS

- HOUSING/REFLECTOR – Precision die-formed 22-gauge C.R.S.
- SHIELDING – Diffuse ribbed acrylic.
- FINISH – Highly reflective non-glare matte white polyester powder coat bonded to phosphate-free, multi-stage pretreated metal. All parts painted after fabrication to facilitate installation, increase efficiency, and inhibit corrosion.
- ELECTRICAL – High quality mid-power LED boards with switchable CCT – 3000K, 3500K, and 4000K. L70 >50,000 hours. fieldselecCCT[®] products use LEDs of multiple CCTs and may produce a perceptibly different shade of white from single-CCT products at the same CCT. All CCTs are within 3 MacAdams ellipses.
- MOUNTING – NEMA Type "G" (1" nominal width grid system only). Drywall kit accessories available, ordered separately.
- LISTINGS –
 - cCSAus certified as luminaire suitable for dry or damp locations.
 - IC-rated for direct contact with insulation.
 - City of Chicago Environmental Air approved when specified with CP option.
- WARRANTY – 5-year limited warranty, see hew.com/warranty.

ORDERING EXAMPLE: PT - 2 4 - L62/8FS - RA - OPTIONS - DIM - UNV

ORDERING INFO

SERIES	WIDTH	LENGTH	LUMENS ^[1]	CRI	CCT	SHIELDING	
PT	1 1' ^[2] 2 2'	2 2' ^[3] 4 4'	1x4	8 80	FS fieldselecCCT 3000K, 3500K, 4000K ^[4]	RA Diffuse ribbed acrylic SA Square acrylic ^[5]	
			L25 2,500lm				
			L37 3,700lm				
	2x2	2 2'	4 4'	L50 5,000lm	8 80	FS fieldselecCCT 3000K, 3500K, 4000K ^[4]	RA Diffuse ribbed acrylic SA Square acrylic ^[5]
				L24 2,400lm			
				L36 3,600lm			
	2x4	2 2'	4 4'	L37 3,700lm	8 80	FS fieldselecCCT 3000K, 3500K, 4000K ^[4]	RA Diffuse ribbed acrylic SA Square acrylic ^[5]
				L55 5,500lm			
				L62 6,200lm			

OPTIONS ^[6]

- EM/7WRM** Remote mount 7-watt emergency battery ^[8]
- EM/10W** 10-watt emergency battery ^[9]
- EM/10WLP** Low-profile 10-watt emergency battery ^[10]
- EM/12W** 12-watt emergency battery ^[11]
- EQCLIPS** Earthquake clips ^[12]
- AMW** Anti-microbial white finish
- CP** Chicago Plenum (CCEA)
- DFK-1248W** Drywall kit, 12" x 48", white
- DFK-2424W** Drywall kit, 24" x 24", white
- DFK-2448W** Drywall kit, 24" x 48", white

CONTROL ^[7]

- DIM** Dimming driver
- DRV** Non-dimming driver
- VDO/DSR** Lutron Vive integral fixture control, RF with daylight and occupancy sensor (DFCSJ-OEM-OCC) and sensor-ready driver ^[13]
- VRF/DSR** Lutron Vive integral fixture control, RF only (DFCSJ-OEM-RF) and sensor-ready driver ^[14]

VOLTAGE

- 120** 120V
- 277** 277V
- UNV** 120-277V
- 347** 347V

QUICKSHIP

2x2	2x4
PT-22-L36/8FS-RA-QS-DIM-UNV	PT-24-L55/8FS-RA-QS-DIM-UNV

NOTES

- ¹ Lumen output based on 3500 CCT. Actual lumens may vary +/-5%, see page 2 for FIXTURE PERFORMANCE DATA.
- ² 4' length only.
- ³ 2' width only.
- ⁴ See page 3 for fieldselecCCT DETAILS.
- ⁵ Increases lumen output by 3%.
- ⁶ See [Technical Info](#) for Drywall Kit details.
- ⁷ See page 3 for ADDITIONAL CONTROL OPTIONS.
- ⁸ 120-277V only.
- ⁹ 120-277V only. 2x2 & 2x4 only.
- ¹⁰ 120-277V only. 1x4 only.
- ¹¹ 120-277V only. 2x2 & 2x4 only.
- ¹² 4 per fixture
- ¹³ See page 3 for SENSOR DETAILS.
- ¹⁴ See page 3 for SENSOR DETAILS.



FIXTURE PERFORMANCE DATA

	LED PACKAGE	DELIVERED LUMENS	WATTAGE	EFFICACY (lm/W)
1x4	L25	2441	19.8	123.2
	L37	3674	30.8	119.3
2x2	L50	4968	42.6	116.7
	L24	2378	20.8	114.3
2x4	L36	3595	30.9	116.5
	L37	3674	30.8	119.3
	L55	5460	47.3	115.5
	L62	6208	54.8	113.3


MULTIPLIER TABLE

COLOR TEMPERATURE	
CCT	CONVERSION FACTOR
3000K	0.94
3500K	1.00
4000K	0.95

- Photometrics tested in accordance with IESNA LM-79. Results shown are based on 25°C ambient temperature.
- Wattage shown is average for 120V through 277V input.
- Results based on 3500K, 80 CRI, actual lumens may vary +/-5%
- Use multiplier table to calculate additional options.

PHOTOMETRY


PT-24-L62/8FS-RA-DIM-UNV Total Luminaire Output: 6208 lumens; 55 Watts | Efficacy: 113 lm/W | 80 CRI; 3500K CCT



VERTICAL ANGLE	HORIZONTAL ANGLE			ZONAL LUMENS
	0°	45°	90°	
0	2375	2375	2375	
5	2339	2336	2323	223
15	2270	2278	2287	638
25	2000	2027	2052	923
35	1617	1668	1711	1041
45	1314	1387	1458	1062
55	956	1046	1130	938
65	619	733	833	724
75	293	451	558	474
85	60	199	228	186
90	0	0	0	

LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 30	1784	29
	0 - 40	2825	46
	0 - 60	4825	78
	0 - 90	6208	100
	0 - 180	6208	100


PT-14-L50/8FS-RA-DIM-UNV Total Luminaire Output: 4969 lumens; 43 Watts | Efficacy: 116 lm/W | 80 CRI; 3500K CCT



VERTICAL ANGLE	HORIZONTAL ANGLE			ZONAL LUMENS
	0°	45°	90°	
0	1811	1811	1811	
5	1852	1831	1804	173
15	1770	1765	1744	495
25	1619	1627	1607	744
35	1409	1427	1428	885
45	1124	1173	1191	895
55	804	884	921	785
65	516	611	627	585
75	229	321	335	326
85	35	58	68	80
90	0	0	0	


LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 30	1413	28
	0 - 40	2298	46
	0 - 60	3978	80
	0 - 90	4969	100
	0 - 180	4969	100

CROSS SECTIONS



FIXTURE DETAILS

BACKVIEW




ADDITIONAL CONTROL OPTIONS

Note: Lumen restrictions apply, consult product builder at hew.com/product-builder.

CATALOG NUMBER	DESCRIPTION
DRV	Driver prewired for non-dimming applications
DIM	Dimming driver prewired for 0-10V low voltage applications
DIM1	1% dimming driver prewired for 0-10V low voltage applications
DIM LINE	Line voltage dimming driver (Must specify 120V or 277V only)
DSR	Sensor-ready driver
SD40	40% step-dimming driver
SD50	50% step-dimming driver
DALI	DALI dimming driver
LTE LINE	Lutron Hi-lume 1% 2-wire dimming driver forward phase line voltage controls (120V only)
LDE1	Lutron Hi-lume 1% EcoSystem dimming LED driver
LDE5	Lutron 5-Series 5% EcoSystem dimming LED driver
VDO/DSR	Lutron Vive integral fixture control, RF with daylight and occupancy sensor (DFCSJ-OEM-OCC) and sensor-ready driver
VRF/DSR	Lutron Vive integral fixture control, RF only (DFCSJ-OEM-RF) and sensor-ready driver
VDO/DBI/LDE1	Lutron Vive integral fixture control, RF with daylight and occupancy sensor (DFCSJ-OEM-OCC), Lutron Hi-lume 1% EcoSystem dimming LED driver, and digital link interface
VDO/DBI/LDE5	Lutron Vive integral fixture control, RF with daylight and occupancy sensor (DFCSJ-OEM-OCC), Lutron 5-Series 5% EcoSystem dimming LED driver, and digital link interface
VRF/DBI/LDE1	Lutron Vive integral fixture control, RF only (DFCSJ-OEM-RF), Lutron Hi-lume 1% EcoSystem dimming LED driver, and digital link interface
VRF/DBI/LDE5	Lutron Vive integral fixture control, RF only (DFCSJ-OEM-RF), Lutron 5-Series 5% EcoSystem dimming LED driver, and digital link interface
ELDO SOLOB	EldoLED Solodrive, 0.1% dimming driver for 0-10V controls
ELDO SOLOB DALI	EldoLED Solodrive, 0.1% dimming driver for DALI controls
ELDO ECO1	EldoLED Ecodrive, 1% dimming driver for 0-10V controls
ELDO ECO1 DALI	EldoLED Ecodrive, 1% dimming driver for DALI controls

fieldselecCCT DETAILS



FLEXIBLE WHIP OPTIONS

All Williams recessed troffers are available with a flexible metallic wiring harness, factory-attached and hard-wired to the luminaire. See ordering information table.

Straight connectors are a snap-in type. Consult factory for wiring harness utilizing connectors secured by lock nuts, optional flex size, lengths, and other wire sizes or circuitry. Three-wire flex utilizes black, white, and green wire. Four-wire flex utilizes black, white, red, and green wire. Adding an emergency option requires an additional wire.

Williams fixtures are UL listed to provide factory-installation of several manufacturers' modular wiring devices. Consult factory for availability and ordering information.

DESIGNATION	DESCRIPTION	DRIVER
F338	6' of 3/8" flex, (3) No. 18 AWG wires with (2) straight connectors	DRV, LTE LINE
F348	6' of 3/8" flex, (4) No. 18 AWG wires with (2) straight connectors	SD40
F334	6' of 3/8" flex, (3) No. 14 AWG wires with (2) straight connectors	DRV, LTE LINE
F344	6' of 3/8" flex, (4) No. 14 AWG wires with (2) straight connectors	SD40
F358	6' of 3/8" flex, (5) #18 AWG wires with (2) straight connectors	DIM, DALI

SENSOR DETAILS

