

CATALOG #: _____

TYPE: _____

PROJECT: _____

FEATURES

- Tunable white from 3000K to 5000K CCT, minimum 80 CRI
- Ambient up/down light with closed top option available
- Fully accessible without the use of tools
- Pull switch and grounded convenience outlet options available
- Optional anti-microbial white finish and pull cord available for use in healthcare applications
- Contoured architectural housing with die-cast aluminum end caps
- Keyhole mounting for easy installation
- Optional tamper-resistant screws available
- Made Right Here® in the USA

SPECIFICATIONS

- **HOUSING** – 20-gauge C.R.S. fixture channel. Front housing constructed of marine grade extruded aluminum with die-cast aluminum end caps.
- **REFLECTIVE SURFACES** – 92% minimum average reflective white polyester powder coat on interior steel components.
- **SHIELDING** – Frosted acrylic, .125" thick.
- **FINISH** – Textured matte white polyester TGIC powder coat bonded to phosphate-free, multi-stage pretreated metal. All parts painted after fabrication to facilitate installation, increase efficiency, and inhibit corrosion.
- **ELECTRICAL** – High quality mid-power LED board. L70 > 50,000 hours per IES TM-21. Tunable White products use LEDs of multiple CCTs and may produce a perceptibly different shade of white from single-CCT products at the same CCT. All CCTs are within 3 MacAdam ellipses.
- **MOUNTING** – Wall.
- **LISTINGS** – cETLus conforms to UL STD 1598 and UL STD 8750. Certified to CAN/CSA STD C22.2 No. 250.0. Suitable for damp locations.
- **WARRANTY** – 5-year limited warranty, see hew.com/warranty.

ORDERING EXAMPLE: WMA - 4 - L64/8TW - AF - OPTIONS - DALI - UNV

ORDERING INFO

SERIES	LENGTH	LUMENS ^[1]	COLOR	SHIELDING
WMA	2 2'	2'	8TW Tunable white (80 CRI, 3000K–5000K)	AF Frosted acrylic, .125" thick
	3 3'	L20 2,000lm		
	4 4'	L30 3,000lm		
		3'		
		L23 2,300lm		
		L46 4,600lm		
	4'			
		L32 3,200lm		
		L64 6,400lm		

OPTIONS ^[2]	CONTROL ^[3]	VOLTAGE
EM/10W 10-watt emergency battery ^[4]	DALI Driver prewired for DALI applications	120 120V
PSBR/120 Single-circuit bottom-mounted pull switch on right ^[5]		277 277V
PSBL/120 Single-circuit bottom-mounted pull switch on left ^[6]	DIM (1) 0-10V signal to control dimming (1) 0-10V signal to control CCT	UNV 120-277V
APCW Anti-microbial white pull cord ^[7]		
GCOR Grounded convenience outlet on left ^[8]	DMX Driver prewired for DMX applications	
GCOR Grounded convenience outlet on right ^[9]		
TP Tamper-resistant (holt head) screws. ^[10]		
LVC1A 1-circuit low-voltage controller, wired for Ambient ^[11]		
LVC3DIM 1-circuit dimming low-voltage controller ^[12]		
AMW Anti-microbial white finish		
(L___) Additional lower lumen packages available. Example: 5,000 lumens = WMA-4-L64/8TW-(L50) ^[13]		
OCC___ Factory-installed occupancy sensor ^[14]		
OCCWS FS-505-PP-___ Low voltage ultrasonic sensor		

NOTES

- ¹ Lumen output based on 4000 CCT. Actual lumens may vary +/-5%, see page 2 for FIXTURE PERFORMANCE DATA. Additional lumen packages available, see Options.
- ² See page 3 for FINISH OPTIONS.
- ³ See page 2 for CONTROL DETAILS.
- ⁴ 4' only
- ⁵ 120V only
- ⁶ 120V only
- ⁷ Packaged with fixture, field installed. Requires PSBR or PSBL option.
- ⁸ 120V only
- ⁹ 120V only
- ¹⁰ This option requires a tamper-resistant tool, must be ordered separately. Please specify quantity required per project.
- ¹¹ 120V or 277V only. Not dimming compatible. Color tuning performed by alternate 0-10V control source.
- ¹² 120V or 277V only. DIM driver only. Bedside switch used to control dimming only, color tuning performed by alternate 0-10V control source.
- ¹³ Specify in increments of 100 nominal lumens. Option must be specified with next higher lumen package.
- ¹⁴ 120V or 277V only, must specify voltage. LVC and OCC options cannot be used simultaneously on 2' and 3' units. See page 2 for FIXTURE DETAILS.




FIXTURE PERFORMANCE DATA

	LED PACKAGE	DELIVERED LUMENS	WATTAGE	EFFICACY (lm/W)
2'	L20	2065	16.8	122.7
	L30	3126	26.2	119.5
3'	L23	2386	19.2	124.2
	L46	4723	39.1	120.8
4'	L32	3318	26.8	123.6
	L64	6511	54.7	119.0

MULTIPLIER TABLE


CCT	CONVERSION FACTOR	
	LUMENS	WATTAGE
3000K	0.95	1.04
3500K	0.98	1.02
4000K	1.00	1.00
5000K	0.96	1.04



- Photometrics tested in accordance with IESNA LM-79. Results shown are based on 25°C ambient temperature.
- Wattage shown is average for 120V through 277V input.
- Results based on 4000K, 80 CRI, actual lumens may vary +/-5%
- Use multiplier table to calculate additional options.

PHOTOMETRY

WMA-4-L64/8TW-AF Total Luminaire Output: 6511 lumens; 54.7 Watts | Efficacy: 119.0 lm/W | 84.2 CRI; 4025K CCT




VERTICAL ANGLE	HORIZONTAL ANGLE					ZONAL LUMENS
	0°	45°	90°	135°	180°	
0	1166	1166	1166	1166	1166	1166
5	1273	1233	1159	1105	1070	110
15	1384	1289	1083	912	838	310
25	1427	1273	952	697	598	454
35	1410	1210	806	510	405	532
45	1313	1077	619	320	228	535
55	1105	869	443	176	101	470
65	890	675	290	67	18	368
75	681	452	145	5	9	260
85	656	394	33	17	33	214
90	598	361	0	31	46	170
95	652	397	35	24	39	216
105	677	458	147	5	9	261
115	884	679	291	64	16	367
125	1096	875	451	179	101	470
135	1296	1077	624	320	228	535
145	1398	1210	820	513	408	533
155	1416	1271	964	700	601	455
165	1380	1290	1099	914	842	311
175	1271	1235	1178	1111	1077	111
180	1169	1169	1169	1169	1169	1169

LUMEN SUMMARY	ZONE	LUMENS	% FIXTURE
	0 - 30	874	13
0 - 40	1407	22	
0 - 60	2411	37	
0 - 90	3253	50	
90 - 120	844	13	
90 - 150	2382	37	
90 - 180	3258	50	
0 - 180	6511	100	

FIXTURE DETAILS

BACKVIEW



	DIMENSIONS		
	A	B	C
2'	25-1/8" O.C.	20-1/2" O.C.	16" O.C.
3'	37-1/8" O.C.	32-1/2" O.C.	32" O.C.
4'	49-1/8" O.C.	42-1/2" O.C.	32" O.C.

OCCUPANCY SENSOR



CONTROL DETAILS

DIM




DALI



DMX



FINISH OPTIONS



For custom color, please specify RAL code or a manufacturer code with description. All custom colors other than RAL require two sample swatches, minimum 1" square.

